


Technical data for trough versions, type: MUK303

1. ***Cargo area volumes m^3***

		Trough length					
		mm	5.200	6.000	6.500	7.000	7.500
Height	1.480						
		17,50 m ³	20,50 m ³	22,00 m ³	23,50 m ³	25,50 m ³	
	1.730						
		20,50 m ³	23,50 m ³	25,50 m ³	27,50 m ³	29,50 m ³	
Height	1.950						
		23,00 m ³	26,50 m ³	29,00 m ³	30,50 m ³	33,50 m ³	
	2.200						
		26,00 m ³	30,00 m ³	32,50 m ³	35,00 m ³	37,50 m ³	
with sidewall extension							
Height	1.980 (1.480 + 500)						
		23,50 m ³	27,00 m ³	29,50 m ³	31,50 m ³	34,00 m ³	
	2.280 (1.480 + 800)						
		27,00 m ³	31,00 m ³	34,00 m ³	36,50 m ³	39,00 m ³	
Height	2.230 (1.730 + 500)						
		26,50 m ³	30,50 m ³	33,00 m ³	35,50 m ³	38,00 m ³	
	2.450 (1.950 + 500)						
		29,00 m ³	33,50 m ³	36,00 m ³	39,00 m ³	41,50 m ³	

2. *Tipping cylinder oil requirement*

	Trough length				
mm	5200	6000	6500	7000	7500
Oil requirement, approx.	30.6 l	32.5 l	34.4 l	34.4 l	34.4 l
For each additional double-acting function (1 cylinder) approx. 1 l					