

Technical data for trough versions, type: MUK303

1. Cargo area volumes m³

		Trough length				
		5.200	6.000	6.500	7.000	7.500
Height	1.480	17,50 m ³	20,50 m ³	22,00 m ³	23,50 m ³	25,50 m ³
	1.730	20,50 m ³	23,50 m ³	25,50 m ³	27,50 m ³	29,50 m ³
	1.950	23,00 m ³	26,50 m ³	29,00 m ³	30,50 m ³	33,50 m ³
	2.200	26,00 m ³	30,00 m ³	32,50 m ³	35,00 m ³	37,50 m ³
with sidewall extension						
Height	1.980 (1.480 + 500)	23,50 m ³	27,00 m ³	29,50 m ³	31,50 m ³	34,00 m ³
	2.280 (1.480 + 800)	27,00 m ³	31,00 m ³	34,00 m ³	36,50 m ³	39,00 m ³
	2.230 (1.730 + 500)	26,50 m ³	30,50 m ³	33,00 m ³	35,50 m ³	38,00 m ³
	2.450 (1.950 + 500)	29,00 m ³	33,50 m ³	36,00 m ³	39,00 m ³	41,50 m ³

2. Tipping cylinder oil requirement

		Trough length				
mm	5200	6000	6500	7000	7500	
Oil requirement, approx.	30.6 l	32.5 l	34.4 l	34.4 l	34.4 l	
For each additional double-acting function (1 cylinder) approx. 1 l						